

Grade 2

Vandal Resistant "Clutch" Cylindrical Leversets

**More Features, More Quality,
More Value! Ideal for
Metal or Wood Doors.**



Universal push-in
and turn button

Extra-sturdy braking
clutch mechanism
for greater durability
and security

UL listed 1/2"
solid brass throw
latch 3-hour fire rated

Cylindrical locking device.
Conforms to ANSI-A 156.2
series 4000. Exceeds
400,000 test cycles.

Concealed screws
for extra security

CSL 8160

Separate spring
mechanism for
each lever, prevents
lever arm sag

**Patented Free Wheeling
Design, Rotates Lever
Up and Down While
Leverset Stays Locked**

**Meets or Exceeds
ADA/ANSI 156.2
Series 4000 Specs.**

The S.Parker "Clutch Leverset" delivers greater value. Now you can inexpensively add extra convenience and less maintenance to any office, factory, school, municipal building or home with this superior clutch leverset. These finely engineered, barrier free leversets are available in one step and two step rose models, in entry, *storeroom or classroom functions*. Ask your S.Parker service representative which function best serves your needs. Once you check the specifications and benefits we think you will agree that these leversets offer you an incredible value.

Outstanding Quality Features:

CSL 8160 – One step rose with two fixed thru-bolt posts outside the standard 2-1/8" cutout (#161 Door Prep) for an extra secure installation, that resists rattling & shaking.

CSL 7160 – Two step rose with convertible posts, allows for standard inside post installation and 2 detachable posts outside the 2-1/8" cutout (#161 Door Prep) for an extra secure installation, where preferred.

2-3/4" Backset and UL Latchbolt – standard for all functions

4-7/8" ANSI Strike – standard with each leverset

6 Pin Solid Brass Cylinder – Keyed to 5. Master Keying Available.

Choice of Over 25 Keyways (refer to chart on reverse side)

Choice of Finishes - US26D Satin Chrome,
US3 Polished Brass or 10B Oil Rubbed Bronze

**Call today... these superior clutch leversets are available
for immediate shipment.**

S.Parker Hardware mfg. corp.

**Your Best Source
For Quality
Door Hardware**

Parker Drive, P.O. Box 9882 1-800-S-PARKER NJ: 201-569-1600
Englewood, New Jersey 07631 FAX: 201-569-1082 NYC: 212-925-6300
EMAIL: www.hardware@sparker.com • Catalog on Web Site: www.sparker.com

Grade 2 Premium "Clutch" Leversets

CSL8160 – Single-Step Rose with Convertible Post
CSL7160 – Two-Step Rose with Fixed Outside Posts



Master and Grand Master Keying Available

Keyways

10 Arrow K2, K6	01 Corbin 59A1	29 Corbin 60	32 Dexter (.216 Comp.) 11929	05 Eagle 11929	14 Falcon 1573, 1577 (.248 Comp.)	05 Harloc 700	02 Harloc SE-L (.216 Comp.)	12 Kwikset (.248 Comp.)
08 Lockwood	05 Lori L100	02 Lori L200 (.216 Comp.)	80 Lori Locksmith Keyway 5 pin	90 "Loricentric" 90 6 pin	11 Russwin 981, 852 (.248 Comp. Reverse)	30 Russwin D1	36 Sargent LA-LC	02 Sargent S (.216 Comp.)
02 Sargent U (.216 Comp.)	04 Schlage C	34 Schlage E	28 Schlage C-K	27 Segal 9	06 Segal (.248 Comp.)	02 Weslock (.216 Comp.)	13 Weiser (.248 Comp.)	03 Yale 8

.248, .216 indicates the first pin location. This allows repinning by duplicating original manufacturers spacing specifications.

Underwriters Laboratories Listings

Listed by Underwriters Laboratories, Inc. for use on fire doors having a rating up to and including 3 hours. These leversets are available with 1/2" throw latchbolts for use in all functions when applied to hollow-metal, metal-clad (Kalamein), composite (with steel and other covering) and sheet-metal type or special treated wood fire doors. It is advisable to check local code authorities, the "Building Materials Directory" published by UL, and the door manufacturer for specific requirements.

- Cylinders** – Solid brass 6 pin tumbler SC-1, ILCO #1145 keyway (keyed to 5). Standard.
- Available Keyways** – Arrow, Corbin, Dexter, Falcon, Harloc, Lockwood, Eagle, Kwikset, Lori, Russwin, Sargent, Segal, Weslock, Weiser, Yale
- Functions** – Entry, Storeroom & Classroom available less cylinder and keys. (LC)
- Housing** – Cold rolled steel and zinc dichromate finish for rust resistance. 2 1/8" diameter bore is required.
- Backset** – 2 3/4" standard. 2 3/8" backsets are available.
- Latch Bolt** – Solid Brass, 1/2" throw for all functions. Housing is in a rust resistant steel-zinc dichromate finish. 1" diameter bore is required.
- Latch Front** – US26D, US 3, US10B finishes 1 1/8" x 2 1/4", beveled 1/8" in 2".
- Strike** – 1 1/4" x 4 7/8" ANSI, box strike has a 1 1/4" lip to center dimension. Brass, bronze or stainless steel.

- Rabbeted** – Fronts and Strikes for 1 3/4" doors.
- Hand** – Reversible, non-handed.
- Door Thickness** – 1 3/8" to 1 3/4" thick.
- Cylinders** – Will accept Lori, AWI or DOM 1x5HT, ASSA or Medeco convert-a-lock cylinders.
- Keys** – Two 5 pin nickel silver keys.
- Finishes** – US26D Satin Chrome, US3 Polished Brass, US10B Oil Rubbed Bronze
- Trim** – Through-bolted assembly through door with separate springs for each lever.
- Packaging** – 1 per box, 10 boxes per carton. Approx. 40 lbs. UPC coded.

When ordering specify series product number, function, finish, strike, latch and keying.

**Your Best Source
For Quality
Door Hardware**

Parker Drive, P.O. Box 9882 1-800-S-PARKER NJ: 201-569-1600
 Englewood, New Jersey 07631 FAX: 201-569-1082 NYC: 212-925-6300
 EMAIL: www.hardware@sparker.com • Catalog on Web Site: www.sparker.com